

Air-Cooled Engines


- Model 006482-0
- Model 006483-0
- Model 006484-0
- Model 006485-0
- Model 006003-0
- Model 006004-0
- Model 006806-0
- Model 006829-0



DESCRIPTION

Scheduled maintenance is a necessity for all standby generators. The Air Cooled Scheduled Maintenance kits offer all the components necessary to perform a complete maintenance on Generac air-cooled generators. Oil will need to be purchased separately based upon the recommendations listed. Maintenance is recommended at every 200 hours or 2 years. If running in a dusty environment, more frequent maintenance may be required. Maintenance intervals may differ per model. Refer to the generator owner's manual for more information.

OIL RECOMMENDATIONS



- SAE 30 above 32° F (0° C)
- 10W-30 between 40° and -10° F (4° and -23° C)
- Synthetic 5W-30 for all temperature ranges

kit compatibility & contents*

Kit Model & UPC	Unit Size	Compatible Unit Models	Air Filter	Oil Filter	AVR Filter	Spark Plug(s)	Oil Funnel	Chamois	Reminder Sticker
006004-0 696471060041	6 kW (530 cc)	5818	•	•		2	•	•	•
006806-0 696471068061	7 kW PowerPact™ (420 cc)	6561	•			1	•	•	•
		6518							
		6519							
006003-0 696471060034	7 kW CorePower™ (432 cc)	5837	•	•		1	•	•	•
		5888							
006482-0 696471064827	8 kW (410 cc)	6237	•	•		1	•	•	•
		6245							
		6251							
006483-0 696471064834	11 kW (530 cc)	6437	•	•		2	•	•	•
		6438							
		6439							
		6440							
		6441							
006484-0 696471064841	13 kW (992 cc)	6254	•	•		2	•	•	•
		6255							
	14 kW (992 cc)	6240							
		6241							
		6247							
	15 kW (992 cc)	6281							
	16 kW (992 cc)	6256							
		6257							
	17 kW (992 cc)	6242							
		6243							
		6248							
6249									
006829-0 696471068290	20 kW Synergy™ (999 cc)	6055	•	•	•	2	•	•	•
	15 kW EcoGen™ (999 cc)	6098							
006485-0 696471064858	20/22 kW (999 cc)	6244	•	•		2	•	•	•
		6250							
		6258							

*Contents of kits may vary. The maintenance kits listed above are for 2013 models only. For maintenance items for older models, please contact a dealer.